

Mid and Hi - Volume Range of Laminators

Seal Image 62 Series – Mid/High Volume Laminator



1575mm wide laminator with 2 x Rollers

Available as 2 x Cold Rollers or 1 x Cold and 1 x Heated Roller for better lamination effect

Hassle free lamination for mid-volume runs

2.5N/mm line pressure

3m/mim lamination speeds

Seal Image 62C x 2 Cold Rollers

POA

Seal Image 62S x Top Roller Heated and Bottom Roller Cold

POA

CREST ES1600 Series – Heavy Duty Laminator Series



1600mm wide laminator with 2 x rollers

Available as 2 x Cold Rollers or 1 x Cold and 1 x Heated Roller for better lamination effect

Robust, industrial design

Perfectly crowned roller technology ensures hassle free long lamination runs and flat mounting

Simple electrical layout (just 2 electronic boards) covering all motor and safety functions ensure easy

4N/mm line pressure for un-paralleled lamination 5m/min lamination speeds

Crest ES1600C x 2 Cold Rollers

POA

Crest ES1600S x Top Roller Heated and Bottom Roller Cold

POA

CREST TS 1400/1600 - UV Output Laminator

The Crest TS 1400/1600 laminator is a machine for high-quality lamination using heat and high pressure. The laminator can be partnered with any UV-curable inkjet printer (suitable for all ink jet and solvent output too).

The machine is special developed to apply a protective laminate on top of UV printed substrates.

The Crest TS 1400/1600 operates without compressed air and accepts boards, sheets and roll material.

- High output speed
- Maximum roll diameters up to 350mm (14 inch)
- Maximum laminating width 1400mm/1600mm (55, 62 inch)
- High laminating pressure
- Digital pressure readout
- Industrial design



Crest TS1600 x 1 Top Hot Roller with fixed temperature control (50°C max)

POA

Crest TS1600 x 1 Top Hot Roller with variable temperature control (0 - 135°C max)

POA

CREST Modular Laminating Concept (MLC) – Up to 2m Wide

The MLC has been designed for high quality adhesive coating, panel mounting, laminating and encapsulating of images. Thanks to the well-developed modular design and the availability of many options and upgrade kits, the machine can be adapted to meet a client's specific needs.

MLC specifications:

- Working width available: 1200, 1400, 1600 or 2000mm
- Laminating rollers: 2 or 4 rollers
- Heatable rollers: 1 or 2 rollers (max. 135°C)
- Winding positions: max. 3 top- and 3 bottom positions
- Laminating speed: 8 m/min
- Other options on request



Crest MLC Series prices upon application...depending on roller width and options.